

TAMRON



70-210_{mm} F/4 VC USD



Reach out and capture the beauty

Partner up with this compact, lightweight, user-friendly telephoto zoom.

Expand your world with each shot

70-210mm F/4 Di VC USD (Model A034)

For Canon and Nikon mounts
Di: For full-frame and APS-C format DSLR cameras



Seize the moment in its true colors

Travel light, Stay focused



Focal Length: 70mm Exposure: F/4.5 1.0sec ISO: 320

The versatile 70-210mm F/4 Di VC USD (Model A034) is the culmination of our years of expertise in telephoto zoom lens development. The A034 has three LD (Low Dispersion) lens elements to correct chromatic aberrations while shooting for clear, crisp images to the edges of the frame. You will also enjoy ultra-soft “bokeh” when shooting up close. Lightweight and compact, this telephoto zoom is ideal for travel. Now you can go lightweight while greatly expanding your shooting possibilities.

Discover the beauty of close-up shooting

With a category-leading* magnification ratio of x0.32, this telephoto zoom lens achieves a MOD of just 0.95m. Get closer to your subjects and feel the freedom of shooting.



Focal Length: 182mm Exposure: F/4.0 1/200sec ISO: 100

Internal zoom combines reliability with stability

An internal zoom mechanism maintains your center of gravity while shooting for more stable performance. Combined with Moisture-Resistant Construction, the internal zoom creates a more comfortable all-around shooting experience. Also, since the total length of the barrel never changes while zooming, you can easily shoot through obstructions such as a wire fence at a zoo.

Excellent AF and reliable VC (Vibration Compensation) performance

The A034 lens includes Tamron’s Dual MPU system: a dedicated MPU (Micro-Processing-Unit) for vibration compensation and another for lens system control, including AF. Each MPU has a DSP (Digital Signal Processing) block for high signal processing that balances reliable vibration compensation with exceptional AF performance. Tamron’s proprietary VC image stabilization features four-stops**. The USD (Ultrasonic Silent Drive) ring-type motor provides excellent response and control for advanced high-speed focusing. Additionally, a full-time manual focus override lets you make fine manual adjustments without having to switch focus modes.



Focal Length: 70mm Exposure: F/4.0 1/4sec ISO: 400

More options. More freedom.

► Optional tripod mount with Arca Swiss type quick-release plate

A solid grip shape combines smart design with ease of carrying. Plus simple attachment and removal allows you to choose the best way to shoot based on your needs.



► TAMRON TAP-in Console™

Optional compatibility with the Tamron’s TAP-in Console (Model TAP-01) lets you easily update firmware and customize the lens by making fine adjustments to AF focusing positions, and more.



► TAMRON TELE CONVERTER

Expand your focal length with your choice of two tele converter options. The TELE CONVERTER 1.4x (Model TC-X14) extends the focal length by 1.4 times, while the TELE CONVERTER 2.0x (Model TC-X20) offers twice the focal length for ultra-telephoto photography.



* TAMRON TELE CONVERTER 2.0x can be used under MF control.

* Among 70-200mm F/4 class interchangeable lenses for full-frame DSLR cameras (as of Jan, 2018; Tamron)

** CIPA Standard Compliant. For Canon: EOS-5D MKIII is used; For Nikon: D810 is used

70-210mm F/4 Di VC USD (Model A034)

Model..... A034	MOD..... 0.95m (37.4 in)	Aperture Blades.....9 (circular diaphragm)	Compatible Mounts..... Canon, Nikon
Focal Length..... 70-210mm	Max. Mag. Ratio..... 1:3.1	Min. Aperture..... F/4-32	
Max. Aperture..... F/4	Filter Size..... ϕ 67mm	Image Stabilization Performance..... 4 Stops (CIPA Standards Compliant) For Canon: EOS-5D MKIII is used/ For Nikon: D810 is used	Specifications, appearance, functionality, etc. are subject to change without prior notice.
Angle of View (diagonal)..... 34°21'-11°46' for full-frame format 23°01'-7°46' for APS-C format	Max. Diameter..... ϕ 76mm	Standard Accessories..... Lens hood, Lens caps	* Length is the distance from the front tip of the lens to the lens mount face. ** Weight does not include the weight of detachable tripod mount.
Optical Construction..... 20 elements in 14 groups	Length*..... 176.5mm (6.9 in) Canon 174mm (6.8 in) Nikon		
	Weight**..... 860g (30.3 oz) Canon 850g (30 oz) Nikon		

Caution: Please read the instruction manual carefully before using the lens.

A34-EN-111-D-1802-0037

TAMRON CO., LTD.

1385, Hasunuma, Minuma-ku,
Saitama-shi, Saitama 337-8556 JAPAN
Tel. +81-48-684-9339
Fax. +81-48-684-9349



Management on Quality and Environment

Tamron is certified with international standards: ISO 9001 for quality and ISO 14001 for environmental management at its headquarters, domestic sales offices, China plant as well as its three production facilities in Aomori, Japan, and is fully committed to striving for continued and sustainable improvement at all levels and facets of its business operations.

